

PRODUCT DATASHEET

LED ECO STREETLIGHT 90 W 3000 K

LED ECO STREETLIGHT HW | Streetlights

□

Areas of application

- Parking
- Gardens
- Residential sector
- Streets
- Road lighting

Product benefits

- High light uniformity and low glare light thanks to precise lens design
- Easy installation thanks pre-wired with mains cable (50 cm)

Product features

- Type of protection: IP66
- Impact resistance: IK08
- High luminous efficacy: up to 130 lm/W
- Available with wattage: 90 W, 120 W, 150 W
- Certificate: CB, RoHS

403 Forbidden

TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 90.00 W |
| Nominal voltage | 100...240 V |
| Mains frequency | 0/50/60 Hz |
| Power factor λ | > 0.90 |
| Protection class | I |

Photometrical data

| | |
|--------------------------------------|--------------|
| Luminous flux | 11250 lm |
| Luminous efficacy | 125 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 5 sdcn |
| Beam angle | 75 ° x 135 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 492.00 mm |
| Width | 196.00 mm |
| Height | 87.00 mm |
| Product weight | 3480.00 g |
| Cable length | 500 mm |

—————
LDECO STREET HE 90W 120W

Materials & Colors

| | |
|-----------------|--------------------|
| Product color | Gray |
| Housing color | Gray |
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

403 Forbidden

Application & Mounting

| | |
|--|--------------|
| Ambient temperature range | -30...+50 °C |
| Temperature range at storage | -40...+70 °C |
| Type of protection | IP66 |
| Protection class IK (shock resistance) | IK08 |
| Dimmable | No |
| Mounting type | Side entry |
| Mounting location | Pole |
| Application environment | Outdoor |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 50000 h ¹⁾ |
| Number of switching cycles | 100000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)


Certificates & Standards


| | |
|----------------------------------|-----------------|
| Standards | CE |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| | |
|-------------|----|
| BEG subsidy | No |
|-------------|----|

DOWNLOAD DATA

| Documents and certificates | Document name |
|---|-------------------------------|
|  User instruction / safety instructions | LDECO STREET HE 90W 120W 150W |

| Photometric and lighting design files | Document name |
|---|----------------------|
|  IES file (IES) | ECO STREET 90W 3000K |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075558120 | Folding box 1 | 582 mm x 128 mm x 253 mm | 3853.00 g | 18.85 dm ³ |
| 4058075558137 | Shipping box 4 | 596 mm x 524 mm x 267 mm | 16810.00 g | 83.39 dm ³ |

403 Forbidden

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

403 Forbidden