

PRODUCT DATASHEET

LDECO CEILING 30W/840 230V

LED ECO CEILING LIGHT (APM) | Wall and ceiling luminaires



Areas of application

- Bedrooms
- Dining rooms
- Terraces
- Corridors

Product benefits

- Homogenous light distribution
- Simple installation
- Low maintenance costs thanks to long lifetime

Product features

- Protection class: I
- Available with wattage: 23 W, 30 W and 42 W
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color consistency: SDCM \leq 6
- Color rendering index R_a : > 80
- Type of protection: IP20
- Certificate: CB, EMC, RoHS



TECHNICAL DATA

Electrical data

| | |
|------------------------|-----------------------|
| Nominal wattage | 30.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Power factor λ | 0.90 |
| Protection class | I |
| Operating mode | Integrated LED driver |

Photometrical data

| | |
|--|----------|
| Luminous flux | 1950 lm |
| Luminous efficacy | 65 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | 4000 K |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 6 sdcm |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 120 ° |
| UGR | < 22 |

Dimensions & Weight

| | |
|----------------|-----------|
| Diameter | 370.00 mm |
| Height | 75.00 mm |
| Product weight | 635.00 g |

LDECO CEILING 30W 230V

Materials & Colors

| | |
|----------------|------------------|
| Product color | White |
| Housing color | White |
| Body material | Metal |
| Cover material | Polystyrene (PS) |

| | |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|


Application & Mounting


| | |
|---------------------------|----------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | Terminal |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Ceiling / Wall |
| Application environment | Indoor |
| Replaceable light source | No |

Certificates & Standards

| | |
|----------------------------------|-----------------|
| Standards | CB / RoHS / EMC |
| Replaceable light source (EPREL) | Not replaceable |

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|-----------------------|
|  | User instruction / safety instructions | LED ECO CEILING LIGHT |

| Photometric and lighting design files | | Document name |
|--|----------------|----------------------------|
|  | IES file (IES) | LDECO CEILING 30W/840 230V |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075581319 | Folding box 1 | 415 mm x 80 mm x 415 mm | 932.00 g | 13.78 dm ³ |
| 4058075581326 | Shipping box 6 | 505 mm x 430 mm x 430 mm | 6312.00 g | 93.37 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

