

PRODUCT DATASHEET

LDPFM SOLAR ST 20.00 W/6500 K

LED PERFORMANCE SOLAR STREETLIGHT | Streetlights



Areas of application

- Streets
- Road lighting
- Rural areas, villages
- Parks
- Areas where no power supply is available

Product benefits

- All-in-one design, no wiring required, flexible installation
- Extremely high system luminous efficacy 185 lm-W to maximize the battery performance
- Rotatable LED module, ensures the light to reach the target surface amply
- Grade A bifacial monocrystalline solar panel, higher sunlight absorbing efficiency than single-sided monocrystalline solar panel
- Adjustable install arm, multi-angle adjustment, make solar panel easy to apply to sunlight trajectory from different directions

Product features

- System wattage 10 W, 20 W, 30 W, 40 W, 50 W and 60 W
- Battery technology: LiFePO4
- Battery overcharge, overdischarge, overheat and short circuit protections
- Available with and without motion sensor
- Meet ME4 road lighting class requirement thanks to professional optical design
- Intelligent controller, rainy day intelligent delay
- Automatically on-off according to brightness of daylight
- Type of protection: IP66



– Certificate: CB

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	3700 lm
Luminous efficacy	185 lm/W
Color temperature	6500 K
Light color (designation)	White
Color rendering index Ra	> 70
Standard deviation of color matching	< 5 sdc _m
Beam angle	30 ° x 150 °

Dimensions & Weight

Length	753.00 mm
Width	358.00 mm
Height	130.00 mm
Product weight	10900.00 g

LDPFM SOLAR ST 20W

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+50 °C
Type of protection	IP66

Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Side entry
Mounting location	Pole
Application environment	Outdoor
LED module replaceable	Not replaceable


BATTERY


Battery size [GMS]	Others
--------------------	--------

Certificates & Standards

Standards	CB
-----------	----

DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction / Safety Instructions	LED PERFORMANCE SOLAR STREETLIGHT

Photometric and lighting design files	Document name
 IES file (IES)	LDPFM SOLAR ST 20W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075562943	Shipping box 1	805 mm x 443 mm x 184 mm	12063.00 g	65.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.