

# PRODUCT DATASHEET

## LDPFM SOLAR ST 30.00 W/3000 K

LED PERFORMANCE SOLAR STREETLIGHT | Streetlights



### Areas of application

- Streets
- Road lighting
- Rural areas, villages
- Parks
- Areas where no power supply is available

### Product benefits

- All-in-one design, no wiring required, flexible installation
- Extremely high system luminous efficacy 185 lm-W to maximize the battery performance
- Rotatable LED module, ensures the light to reach the target surface amply
- Grade A bifacial monocrystalline solar panel, higher sunlight absorbing efficiency than single-sided monocrystalline solar panel
- Adjustable install arm, multi-angle adjustment, make solar panel easy to apply to sunlight trajectory from different directions

### Product features

- System wattage 10 W, 20 W, 30 W, 40 W, 50 W and 60 W
- Battery technology: LiFePO4
- Battery overcharge, overdischarge, overheat and short circuit protections
- Available with and without motion sensor
- Meet ME4 road lighting class requirement thanks to professional optical design
- Intelligent controller, rainy day intelligent delay
- Automatically on-off according to brightness of daylight
- Type of protection: IP66



– Certificate: CB

## TECHNICAL DATA

### Electrical data

Nominal wattage	30.00 W
Protection class	III
Operating mode	Battery

### Photometrical data

Luminous flux	5550 lm
Luminous efficacy	185 lm/W
Color temperature	3000 K
Light color (designation)	White
Color rendering index Ra	> 70
Standard deviation of color matching	< 5 sdc <sub>m</sub>
Beam angle	30 ° x 150 °

### Dimensions & Weight

Length	897.00 mm
Width	358.00 mm
Height	130.00 mm
Product weight	12900.00 g

LDPFM SOLAR ST 30W

### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	0...+50 °C
Type of protection	IP66

Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Side entry
Mounting location	Pole
Application environment	Outdoor

**BATTERY**

Battery size [GMS]	Others
--------------------	--------


**Certificates & Standards**


Standards	CB
Replaceable light source (EPREL)	Not replaceable

**Additional product data**

BEG subsidy	No
-------------	----

**DOWNLOAD DATA**

Documents and certificates		Document name
	User instruction / safety instructions	LED PERFORMANCE SOLAR STREETLIGHT

Photometric and lighting design files		Document name
	IES file (IES)	LDPFM SOLAR ST 30W

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075562950	Shipping box 1	950 mm x 443 mm x 184 mm	14650.00 g	77.44 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.