

PRODUCT DATASHEET

LED VALUE CEILING 10 W 6500 K

LED VALUE CEILING GEN4 | Wall and ceiling luminaires



Areas of application

- Bedrooms
- Dining rooms
- Balcony
- Corridors

Product features

- Protection class: I
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): up to 30,000 h
- Color consistency: SDCM 5
- Color rendering index R_a : ≥ 80
- Beam angle: 120°
- Surge voltage capability: 1 kV



TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	100...240 V
Mains frequency	50...60 Hz
Nominal current	90.000 mA
Protection class	I

Photometrical data

Luminous flux	800 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80
Beam angle	120 °

Dimensions & Weight

Diameter	260.00 mm
Height	60.00 mm
Product weight	362.00 g

LDVAL CEILING 10W 100-240V G4

Materials & Colors




Product color	White
Housing color	White
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting

Type of connection	Terminal
Type of protection	IP20

Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
LED module replaceable	Not replaceable

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction / Safety Instructions	LED VALUE CEILING
Photometric and lighting design files		Document name
	IES file (IES)	LDVALCEILING10W 100-240V G4
	LDT file (Eulumdat)	LDVALCEILING10W 100-240V G4

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075519879	Folding box 1	285 mm x 285 mm x 66 mm	550.00 g	5.36 dm ³
4058075519886	Shipping box 5	350 mm x 300 mm x 310 mm	3250.00 g	32.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.