

PRODUCT DATASHEET LED VALUE CEILING 20 W 4000 K

LED VALUE CEILING GEN4 | Wall and ceiling luminaires



Areas of application

- Bedrooms
- Dining rooms
- Balcony
- Corridors

Product features

- Protection class: I
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): up to 30,000 h
- Color consistency: SDCM 5
- Color rendering index Ra: ≥ 80
- Beam angle: 120°
- Surge voltage capability: 1 KV



TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	100240 V
Mains frequency	5060 Hz
Nominal current	180.000 mA
Protection class	1
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1600 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Beam angle	120 °

Dimensions & Weight

Diameter	330.00 mm
Height	65.00 mm
Product weight	546.00 g

LDVAL CEILING 20W/23W 100-240V G4

Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting

Type of connection	Plug, quick disconnect

Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LED VALUE CEILING	

Photometric and lighting design files	Document name
IES file (IES)	LDVALCEILING20W 100-240V G4
LDT file (Eulumdat)	LDVALCEILING20W 100-240V G4

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075519916	Folding box 1	370 mm x 370 mm x 71 mm	880.00 g	9.72 dm ³
4058075519923	Shipping box 5	385 mm x 375 mm x 395 mm	5120.00 g	57.03 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.