

PRODUCT DATASHEET LED ECO Hi-Watt 175 30 W/3000 K E27

LED ECO HIGH WATT | T shape bulb



Areas of application

- Especially suitable for the food sector
- Warehouses
- Supermarkets and department stores
- Suitable for indoor applications.

Product benefits

- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam

Product features

- Lifetime: up to 12,000 h
- Good color rendering index R_a : ≥ 80
- Overtemperature protection
- Surge protection: up to 2,000 V
- $-\,$ Luminous efficacy: up to 100 lm/W
- Mercury-free lamps
- Minimum start voltage at 180 VAC



TECHNICAL DATA

Electrical data

Nominal wattage	30 W
Construction wattage	30.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	175 W
Nominal current	245 mA
Type of current	AC
Operating frequency	50 Hz
Mains frequency	50 Hz
Power factor λ	0.50

Photometrical data

Luminous flux	2700 lm
Nominal useful luminous flux 90°	2700 lm
Luminous efficacy	90 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	180 °
Starting time	< 0.5 \$

Dimensions & Weight

Overall length	158.00 mm
Diameter	100.00 mm
Maximum diameter	100 mm

Temperatures & operating conditions	110.00 g
Ambient temperature range	
7 whole temperature range	-20+40 °C
Lifespan	
Number of switching cycles 1	100000
Additional product data	
Base (standard designation)	E27
Mercury content 0	0.0 mg
Capabilities	
Dimmable	No
Certificates & Standards	
Standards	CB / RoHS
Country-specific categorizations	
Order reference L	LE HW 30W/830 2
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27
Length 1	158.00 mm

LOGISTICAL DATA

Height

Width

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075683112	Folding box 1	107 mm x 107 mm x 170 mm	162.00 g	1.95 dm ³
4058075683129	Shipping box 10	551 mm x 230 mm x 197 mm	2131.00 g	24.97 dm ³

100.00 mm

100.00 mm

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

September 10, 2025, 23:48:49 LED ECO Hi-Watt 175 30 W/3000 K E27

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.