

PRODUCT DATASHEET

LED VALUE CANOPY MRE 110W 865 W

LED VALUE CANOPY LIGHT | High-bay luminaires



Areas of application

- Petrol station
- Indoor low-high space ceiling applications
- Logistics halls
- Canopy lighting

Product benefits

- Low maintenance costs thanks to long lifetime
- Pre-wired with mains cable

Product features

- Available with wattage: 60 W, 90 W and 110 W
- Available in surface mounting, recessed mounting and pole mounting
- System efficacy 135 lm/W provides high energy saving compare to conventional HID product
- Beam angle: symmetric middle (90°), symmetric wide (120°), asymmetric (120° x 60°)
- Die cast aluminum housing provides good heat dissipation
- Secondary optics - tempered glass cover, helps to ensure the stability of product performance
- Type of protection: IP66
- Impact resistance: IK07
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- Color consistency: SDCM <5



– Certificate: CB, EMC, RoHS

TECHNICAL DATA

Electrical data

Nominal wattage	110.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I

Photometrical data

Luminous flux	14850 lm
Luminous efficacy	135 lm/W
Color temperature	6500 K
Standard deviation of color matching	< 5 sdcn
Beam angle	120 °

Dimensions & Weight

Length	400.00 mm
Width	400.00 mm
Height	90.00 mm
Product weight	6300.00 g

LDVAL CANOPY MRE 90W_110W

Materials & Colors

Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Type of protection	IP66
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Outdoor

LED module replaceable	Not replaceable
------------------------	-----------------

Certificates & Standards

Standards	CB
-----------	----

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075538320	Shipping box 1	450 mm x 450 mm x 125 mm	7173.00 g	25.31 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.