

PRODUCT DATASHEET

LED VALUE CANOPY MSF 110W 865 W

LED VALUE CANOPY LIGHT | High-bay luminaires



Areas of application

- Petrol station
- Indoor low-high space ceiling applications
- Logistics halls
- Canopy lighting

Product benefits

- Low maintenance costs thanks to long lifetime
- Pre-wired with mains cable

Product features

- Available with wattage: 60 W, 90 W and 110 W
- Available in surface mounting, recessed mounting and pole mounting
- System efficacy 135 lm/W provides high energy saving compare to conventional HID product
- Beam angle: symmetric middle (90°), symmetric wide (120°), asymmetric (120° x 60°)
- Die cast aluminum housing provides good heat dissipation
- Secondary optics - tempered glass cover, helps to ensure the stability of product performance
- Type of protection: IP66
- Impact resistance: IK07
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- Color consistency: SDCM <5



– Certificate: CB, EMC, RoHS

TECHNICAL DATA

Electrical data

Nominal wattage	110.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Total harmonic distortion	< 20 %
Protection class	I

Photometrical data

Luminous flux	14850 lm
Luminous efficacy	135 lm/W
Color temperature	6500 K
Standard deviation of color matching	< 5 sdc _m
Beam angle	120 °

Dimensions & Weight

Length	302.00 mm
Width	302.00 mm
Height	93.00 mm
Product weight	3900.00 g

LDVAL CANOPY MSF 90W_110W

Materials & Colors

Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Type of protection	IP66
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Pole

Application environment	Outdoor
-------------------------	---------

Certificates & Standards

Standards	CB
Replaceable light source (EPREL)	Not replaceable

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075539440	Shipping box 1	362 mm x 362 mm x 122 mm	4488.00 g	15.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.