

PRODUCT DATASHEET

SMART+ Wifi Ceiling Fan LED Round 550mm + RC

Smart+ wifi ceiling fan | Smart Wifi Ceiling fans for various application areas, combining light and air ventilation



Areas of application

- Kitchens, living rooms, children's rooms or home offices
- For indoor use only

Product benefits

- Clean design, allows for an easy combination with various room styles
- Easy mounting

Product features

- Network protocol: WiFi
- Luminaire with integrated air ventilation
- Adjustable air speed
- Smart control for adjustable color temperature
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Remote control included for network independent operation



TECHNICAL DATA

Electrical data

Nominal wattage	75.00 W
Nominal voltage	3,6 V
Mains frequency	50...60 Hz
Nominal current	10.000 mA
Max. number of luminaires per miniature circuit breaker B16	21
Power factor λ	> 0.90
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	3000 lm
Total luminous flux of contained light sources	4100 lm
Luminous efficacy	131 lm/W
Color temperature	3000...6500 K
Reference control setting of contained light source (Kelvin)	3000 K ¹⁾
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc _m
Flickering metric (Pst LM)	≤1
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	100 °
UGR	< 25

1) Performing a reset will restore the default values set by the manufacturer

Dimensions & Weight

Length	602.00 mm
Width	600.00 mm
Height	216.00 mm
Product weight	3000.00 g

SMART WIFI CEILING FAN RD REM
TW WT

Materials & Colors

Product color	White
Housing color	White
Body material	Acrylonitrile butadiene styrene (ABS)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

BEG eligible

No





EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Remote control included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
	User Instruction / Safety Instructions	SMART WIFI CEILING FAN
	Declarations of conformity	SMART WIFI CEILING FAN RD REM TW WT
	Declarations of conformity	SMART WIFI CEILING FAN TW
	Declarations Of Conformity UKCA	SMART WIFI

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075572553	Folding box 1	216 mm x 600 mm x 602 mm	3688.00 g	78.02 dm ³
4058075572560	Shipping box 2	620 mm x 452 mm x 620 mm	9235.00 g	173.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.