

PRODUCT DATASHEET SMART+ Wifi Orbis Spiral White 500mm TW

Spiral | Decorative ceiling luminaires with WiFi technology

Areas of application

- Indoor applications

- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Easy and quick installation

Product features

- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)



TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	177.000 mA
Power factor λ	> 0.50
Total harmonic distortion	< 20 %
Protection class	1
Operating mode	Mains voltage


Photometrical data

Luminous flux	1900 lm	
Total luminous flux of contained light sources	4060 lm	
Luminous efficacy	102 lm/W	
Color temperature	30006500 K	
Reference control setting of contained light source (Kelvin)	3000 K ¹⁾	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG1	
Photobiological safety group acc. to EN62471	RG1	
Beam angle	161.00 °	

1) Performing a reset will restore the default values set by the manufacturer

Dimensions & Weight

Diameter	500.00 mm
Height	66.00 mm
Product weight	4000.00 g



Materials & Colors

Product color	White	
Housing color	White	
Body material	Polymethylmethacrylate (PMMA)	
Cover material Polymethylmethacrylate (PMMA)		
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Screw terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	SMART ORBIS SPIRAL	
POF	Legal information	Legal insert SUNATHOME WORKSPACE	
POF	Declarations of conformity	SMART WIFI ORBIS SPIRAL RD500 TW WTLEDV	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075486607	Folding box 1	76 mm x 542 mm x 544 mm	4411.00 g	22.41 dm ³
4058075486614	Shipping box 3	565 mm x 247 mm x 568 mm	14277.00 g	79.27 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.