

PRODUCT DATASHEET

LED PERFORMANCE HIGHBAY 200W 865

LED PERFORMANCE HIGHBAY | High-bay luminaires



Areas of application

- Industry
- Commercial lighting
- Warehouses
- Public areas (stations, stadiums)
- Airports

Product benefits

- Energy savings thanks to system efficacy 160 lm/W
- UV resistant PC lens offer a durable service
- Low maintenance costs thanks to long lifetime

Product features

- Available with different wattage: 100 W, 150 W, 200 W
- Input voltage: 100 - 277V AC
- Standard CCT: 6500 K and 4000 K
- Color rendering index $R_a \geq 80$
- Power factor: ≥ 0.9
- Luminous efficacy: up to 160 lm/W
- Lifetime (L70/B50): 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK08
- Pre-wired with 500mm cable
- Die-cast aluminum housing
- Safety compliance certificates: CB, EMC, RoHS 2.0

TECHNICAL DATA

Electrical data

Nominal wattage	200.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Max. number of luminaires per miniature circuit breaker B16	2
Max. number of luminaires per miniature circuit breaker C16	3
Power factor λ	0.90
Total harmonic distortion	< 20 %
Protection class	I

Photometrical data

Luminous flux	32000 lm
Luminous efficacy	160 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	< 5 sdcn
Photobiological safety group acc. to EN62778	RG1

Dimensions & Weight

Diameter	336.00 mm
Height	122.00 mm
Product weight	2865.00 g



LDPFM HIGHBAY

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum

Application & Mounting

Ambient temperature range	-30...+50 °C
---------------------------	--------------

Type of protection	IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan


Lifespan L70/B50 at 25 °C	100000 h ¹⁾
---------------------------	------------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CB / EMC / ROHS / SASO
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDPFM HB DALI 200W 865 G4

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075726017	Shipping box 1	384 mm x 384 mm x 169 mm	3650.00 g	24.92 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.