

# PRODUCT DATASHEET

## LED PERFORMANCE HIGHBAY 150W 840

LED PERFORMANCE HIGHBAY | High-bay luminaires



### Areas of application

- Industry
- Commercial lighting
- Warehouses
- Public areas (stations, stadiums)
- Airports

### Product benefits

- Energy savings thanks to system efficacy 160 lm/W
- UV resistant PC lens offer a durable service
- Low maintenance costs thanks to long lifetime

### Product features

- Available with different wattage: 100 W, 150 W, 200 W
- Input voltage: 100 - 277V AC
- Standard CCT: 6500 K and 4000 K
- Color rendering index  $R_a \geq 80$
- Power factor:  $\geq 0.9$
- Luminous efficacy: up to 160 lm/W
- Lifetime (L70/B50): 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK08
- Pre-wired with 500mm cable
- Die-cast aluminum housing
- Safety compliance certificates: CB, EMC, RoHS 2.0

## TECHNICAL DATA

### Electrical data

Nominal wattage	150.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Max. number of luminaires per miniature circuit breaker B16	6
Max. number of luminaires per miniature circuit breaker C16	9
Power factor $\lambda$	0.90
Total harmonic distortion	< 20 %
Protection class	I

### Photometrical data

Luminous flux	24000 lm
Luminous efficacy	160 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	< 5 sdcn
Photobiological safety group acc. to EN62778	RG1

### Dimensions & Weight

Diameter	298.00 mm
Height	119.00 mm
Product weight	2200.00 g



LDPFM HIGHBAY

### Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum

### Application & Mounting

Ambient temperature range	-30...+50 °C
---------------------------	--------------

Type of protection	IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Application environment	Indoor
With light source	Yes
Replaceable light source	No

### Lifespan


Lifespan L70/B50 at 25 °C	100000 h <sup>1)</sup>
---------------------------	------------------------

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CB / EMC / ROHS / SASO
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

### DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDPFM HB DALI 150W 840 G4

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075726093	Shipping box 1	346 mm x 346 mm x 164 mm	3000.00 g	19.63 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.