

PRODUCT DATASHEET LED PFM CLAS A 60 6.5 W/2700 K B22d

LED DAYLIGHT SENSOR CLASSIC A | Special LED lamps with daylight sensor, classic bulb shape



Areas of application

- Outdoor use in suitable outdoor luminaires only
- Wherever constant lighting is necessary at night

Product benefits

- Short payback period thanks to low energy consumption and maintenance costs
- Energy-saving lighting solution because of automatic switch-off at daylight
- Safety through automatic switch-on at darkness
- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- Light sensors detect daylight on the basis of the spectral distribution

Product features

- LED alternative to conventional lamps
- High color consistency: ≤ 6 SDCM
- Mercury-free lamps



TECHNICAL DATA

Electrical data

| Nominal wattage | 6.5 W |
|--|----------|
| Construction wattage | 6.50 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 60 W |
| Nominal current | 50 mA |
| Type of current | AC |
| Operating frequency | 5060 Hz |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.50 |

Photometrical data

| Luminous flux | 806 lm |
|---|------------|
| Luminous efficacy | 124 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |

Light technical data

| Beam angle | 300 ° |
|---------------|---------|
| Starting time | < 0.5 s |

Dimensions & Weight

| Overall length | 104.00 mm |
|------------------|-----------|
| Diameter | 60.00 mm |
| Maximum diameter | 60 mm |
| Product weight | 31.00 g |

Temperatures & operating conditions

Lifespan

| Number of cuttaking avalag | 100000 |
|---|--|
| Number of switching cycles | 100000 |
| Additional product data | |
| Base (standard designation) | B22d |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
| Capabilities | |
| Dimmable | No |
| Certificates & Standards | |
| Type of protection | IP20 |
| Country-specific categorizations | |
| Order reference | LPCLA60DS 6,5W/ |
| Energy labelling regulation data acc EU 2019/2015 | |
| Light source cap-type (or other electric interface) | B22d |
| Length | 104.00 mm |
| Height | 60.00 mm |
| Width | 60.00 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075505407 | Folding box | 60 mm x 60 mm x 144 mm | 47.00 g | 0.52 dm ³ |
| 4058075505414 | Shipping box 10 | 315 mm x 131 mm x 126 mm | 566.00 g | 5.20 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.