

# PRODUCT DATASHEET

## SUBSTITUTE ECO DE T8 WITH SAFETY GUARD PIN 9 W/3000 K 600 MM

SUBSTITUTE ECO T8 | Double-ended LED T8 with Safety Guard Pin



---

### Areas of application

- Train stations
- Offices
- Underground stations
- Supermarkets and department stores
- Parking lots, warehouses, production areas, stairways

---

### Product benefits

- High luminous flux for sophisticated lighting tasks
- Easy installation
- High luminous efficacy compared with standard lamps

---

### Product features

- T8 LED tube made of glass with G13 base
- Double-end input design
- Mercury-free lamps
- Type of protection: IP20

## 403 Forbidden

---

## TECHNICAL DATA

### Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Nominal current	70 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz

### Photometrical data

Luminous flux	900 lm
Luminous efficacy	100 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830
Standard deviation of color matching	≤6 sdcn

### Light technical data

Starting time	< 0.5 s
---------------	---------

### Dimensions & Weight

Overall length	600.00 mm
Diameter	28.00 mm
Maximum diameter	28 mm
Product weight	96.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	<75 °C

### Lifespan

Number of switching cycles	50000
----------------------------	-------

### Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg

# 403 Forbidden

Mercury-free	Yes
Design / version	Frosted

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Type of protection	IP20
Standards	ROHS / EMC

### Country-specific categorizations

Order reference	ST8E-0.6M 9W/83
-----------------	-----------------




### LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	600.00 mm
Height	28.00 mm
Width	28.00 mm

### DOWNLOAD DATA

	Photometric and lighting design files	Document name
	IES file (IES)	ST8E 0.6M 9W 830 230VAC DE
	LDT file (Eulumdat)	ST8E 0.6M 9W 830 230VAC DE
	Light distribution curve type polar	ST8E 0.6M 9W 830 230VAC DE

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854204968	Sleeve 1	610 mm x 28 mm x 28 mm	127.00 g	0.48 dm <sup>3</sup>
4099854204975	Shipping box 25	660 mm x 167 mm x 185 mm	4156.00 g	20.39 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

## 403 Forbidden

When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**403 Forbidden**