

## PRODUCT DATASHEET

### SUBSTITUBE ECO DE T8 WITH SAFETY GUARD PIN 9 W/6500 K 600 MM

SUBSTITUBE ECO T8 | Double-ended LED T8 with Safety Guard Pin



#### Areas of application

- Train stations
- Offices
- Underground stations
- Supermarkets and department stores
- Parking lots, warehouses, production areas, stairways

#### Product benefits

- High luminous flux for sophisticated lighting tasks
- Easy installation
- High luminous efficacy compared with standard lamps

#### Product features

- T8 LED tube made of glass with G13 base
- Double-end input design
- Mercury-free lamps
- Type of protection: IP20



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Nominal current	70 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz

**Photometrical data**

Luminous flux	1000 lm
Luminous efficacy	111 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcn

**Light technical data**

Starting time	< 0.5 s
---------------	---------

**Dimensions & Weight**

Overall length	600.00 mm
Diameter	28.00 mm
Maximum diameter	28 mm
Product weight	96.00 g

**Temperatures & operating conditions**

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	<75 °C

**Lifespan**

Number of switching cycles	50000
----------------------------	-------

**Additional product data**

Base (standard designation)	G13
Mercury content	0.0 mg

Mercury-free	Yes
Design / version	Frosted

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection	IP20
Standards	ROHS / EMC

Country-specific categorizations

Order reference	ST8E-0.6M 9W/86
-----------------	-----------------




LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	600.00 mm
Height	28.00 mm
Width	28.00 mm

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	ST8E 0.6M 9W 865 230VAC DE
	LDT file (Eulumdat)	ST8E 0.6M 9W 865 230VAC DE
	Light distribution curve type polar	ST8E 0.6M 9W 865 230VAC DE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854205064	Sleeve 1	610 mm x 28 mm x 28 mm	127.00 g	0.48 dm <sup>3</sup>
4099854205071	Shipping box 25	660 mm x 167 mm x 185 mm	4156.00 g	20.39 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.