

PRODUCT DATASHEET

LED ECO LITE DAMP PROOF HOUSING

DE1200

LED ECO LITE DAMP PROOF HOUSING | Damp-proof luminaires

Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines



Product benefits

- UV-stabilized polycarbonate opal diffuser for uniform light distribution and long durability
- Polycarbonate body and diffuser offers IK08 impact protection
- VDE certified components ensure product reliability

Product features

- Class II luminaire
- Two versions for IEC62776 single ended LED tubes and double ended LED tubes
- PG13.5 cable gland
- Classic design with PC body and PC diffuser
- Type of protection: IP65
- Impact resistance: IK08

TECHNICAL DATA

Dimensions & Weight

Length	1277.00 mm
Width	109.00 mm
Height	67.00 mm
Product weight	1005.00 g



LED ECO LITE DP HOUSING


Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Plastic

Application & Mounting

Dimmable	No
Mounting type	Surface/Suspended
Application environment	Indoor

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LDE LITE DP DE 1200 2XLAMP HOUSING

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854110306	Folding box 1	112 mm x 69 mm x 1,279 mm	1073.00 g	9.88 dm ³
4099854110313	Shipping box 8	1,300 mm x 240 mm x 305 mm	9664.00 g	95.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.