

# PRODUCT DATASHEET ST8V-0.6M 8 W/6500 K 600 mm

SubstiTUBE T8 EM VALUE | Value LED tubes for electromagnetic control gears (CCG)



#### Areas of application

- Train stations
- Offices
- Underground stations
- Supermarkets and department stores
- Parking lots & Alleys
- Warehouses

### Product benefits

- Quick, simple and safe replacement of fluorescent lamps without rewiring the CCG
- Realistic color rendering thanks high color saturation and excellent color rendering index
- Outstanding quality of light
- Lower maintenance cost thanks to longer lifetime than traditional Fluorescent
- Correct operation even at low temperatures
- RoHS-conformity
- Mercury-free
- High color rendition (Ra≥80) with excellent color fidelity for a true lighting effect

#### **Product features**

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires
- Lifetime up to 30,000 h
- High luminous efficacy: up to 112 lm/W



# TECHNICAL DATA

# Electrical data

Nominal wattage	8 W
Nominal voltage	230 V
Nominal current	60 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

# Photometrical data

Luminous flux	900 lm
Luminous efficacy	112 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	> 80
Light color	865
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	› 160.00 °
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	604.00 mm
Diameter	28.00 mm
Product weight	52.00 g

# Temperatures & operating conditions

Ambient temperature range -2	-20+45 °C
------------------------------	-----------

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	100000

# Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg

Mercury-free	Yes	
0 1 1 11111		
Capabilities		
Dimmable	No	
Certificates & Standards		
Type of protection	IP20	
Country-specific categorizations		
Order reference	ST8V-0.6M 8W/86	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Light source cap-type (or other electric interface)	G13	
Length	604.00 mm	

#### DOWNLOAD DATA

Height

Width

Photometric and lighting design files Document name		Document name	
	IES file (IES)	ST8V0.6M 8W865 230V EM PC	
	LDT file (Eulumdat)	ST8V0.6M 8W865 230V EM PC	
Light distribution curve type polar ST8V0.6M 8W865 230V EM PC		ST8V0.6M 8W865 230V EM PC	

28.00 mm

28.00 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854309588	Sleeve 1	670 mm x 28 mm x 28 mm	63.00 g	0.53 dm <sup>3</sup>
4099854309595	Shipping box 25	722 mm x 158 mm x 176 mm	2459.00 g	20.08 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.