

PRODUCT DATASHEET

LDVAL STREET MD 150W 730 G3

LED VALUE STREETLIGHT G3 | Streetlights



Areas of application

- Roadway
- Streets
- Highways
- Parking
- Area lighting

Product benefits

- Smooth housing surface makes the fixture dust-free and easy cleaning
- High grade die cast aluminum housing ensures reliable operation
- Professional lighting distribution provides uniformity lighting
- Gear box tool-less open and tilt setting -15°~15° for easy installation
- Energy savings thanks to system efficacy of up to 140lm/W

Product features

- Available in 30W, 55W, 70W, 90W, 120W, 150W, 180W, 200W and 230W
- On/off version and 1-10V dimming version (with NEMA socket) available
- UV stabilized polycarbonate lens
- Secondary optics - tempered glass cover, helps to ensure the stability of product performance
- Surge protection: up to 10 kV (L-N)
- Adjustable spigot for both side-entry and post-top installation
- Type of protection: IP66
- Impact resistance: IK08
- CB certification done by authorized institution

TECHNICAL DATA

Electrical data


Nominal wattage	150.00 W
Nominal voltage	120...277 V
Protection class	I

Photometrical data

Luminous flux	19500 lm
Luminous efficacy	130 lm/W
Color temperature	3000 K

Dimensions & Weight

Length	644.00 mm
Width	274.00 mm
Height	99.00 mm
Product weight	5420.00 g



LDVAL STREET MD

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum


Application & Mounting


Type of protection	IP66
Dimmable	No
Application environment	Outdoor

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LDVAL STREET

Photometric and lighting design files		Document name
	IES file (IES)	LDVAL STREET MD 150W 730 NM G3

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854189586	Shipping box 1	588 mm x 332 mm x 190 mm	6262.00 g	37.09 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.