


PRODUCT DATASHEET

LED VALUE PANEL BACKLIT G2 0606 | Recessed panel luminaires



Product benefits

- Value for money luminaire
- Low flicker light thanks to special electronic control gear
- External driver for extended flexibility and easy installation
- Versions with DALI ECG available

TECHNICAL DATA

Electrical data

Nominal wattage	33.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Protection class	II

Photometrical data

Luminous flux	4000 lm
Luminous efficacy	120 lm/W
Color temperature	6500 K
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdc _m
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

Dimensions & Weight

Length	595.00 mm
Width	595.00 mm
Height	32.00 mm
Product weight	1650.00 g

LDVAL PL0606B UGR

Materials & Colors

Body material	Steel
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP54
Dimmable	No
Mounting type	Recessed/Suspended/Surface
Application environment	Indoor

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / RoHS
Replaceable light source (EPREL)	Not replaceable

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854031779	Folding box 1	643 mm x 605 mm x 37 mm	2371.00 g	14.39 dm ³
4099854031786	Shipping box 6	690 mm x 237 mm x 659 mm	15257.00 g	107.77 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.