

PRODUCT DATASHEET LDSUP SMART+PRO SP 9W TW 36D BT

LED SUPERIOR SMART+PRO SPOTLIGHT 2 CHANNEL | Spotlights



Product benefits

- Suitable luminaire for SMART+PRO BLE Mesh light management system with low power, highly scalable and stable ecosystem
- External driver for extended flexibility and easy installation
- 2 output current channels for tunable white application

Product features

- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Available in 36° and 60° beam angles
- Available in 9 W and 13 W
- Long lifetime up to 50,000 h
- LEDVANCE SMART+PRO app required for commissioning of the SMART+PRO system only (available for Android and iOS)

TECHNICAL DATA

Electrical data

| Nominal wattage | 9.00 W |
|------------------------|----------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 200 mA |
| Power factor λ | > 0.80 |

Photometrical data

| Luminous flux | 855 lm |
|--------------------------|---------------|
| Luminous efficacy | 95 lm/W |
| Color temperature | Tunable White |
| Color rendering index Ra | 90 |
| Beam angle | 36 ° |

Dimensions & Weight

| Diameter | 110.00 mm |
|----------------|-----------|
| Height | 49.50 mm |
| Product weight | 368.00 g |



Application & Mounting

| Type of protectionIP20DimmableYesType of dimmingBluetooth | Ambient temperature range | -20+45 °C |
|---|---------------------------|-----------|
| | Type of protection | IP20 |
| Type of dimming Bluetooth | Dimmable | Yes |
| | Type of dimming | Bluetooth |
| Replaceable light source No | Replaceable light source | No |

Lifespan

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|
|----------------------------------|-----------------|

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854434211 | Folding box 1 | 137 mm x 127 mm x 112 mm | 436.00 g | 1.95 dm ³ |
| 4099854434228 | Shipping box 30 | 396 mm x 286 mm x 585 mm | 13785.00 g | 66.25 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.