

# PRODUCT DATASHEET

## LDPFM LN HO 1200 50W TRI8

LINEAR HIGH OUTPUT GEN 2 | Surface luminaire with TRI-CCT and high luminous efficacy up to 150 lm/W



---

### Product benefits

- Replacement of conventional T8 tubes with up to 7500 lm (1.2 m version) and up to 10500 lm (1.5 m version)
- Energy savings up to 70 % (compared to luminaires that use fluorescent lamps)
- Robust structure with IK08
- Easy installation and versatile application
- 5 years guarantee

---

## TECHNICAL DATA

### Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz

### Photometrical data

Color temperature	3000 K / 4000 K / 6500 K
Color rendering index Ra	> 80
Beam angle	120 °

### Dimensions & Weight

Length	1168.00 mm
Width	65.00 mm
Height	74.00 mm
Product weight	1160.00 g

LDPFM LN HO 1200 50W TRI8

### Materials & Colors

Body material	Metal Steel
---------------	-------------

### Application & Mounting


Type of protection	IP20
Dimmable	No
Replaceable light source	No

### Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

---

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LDPFM LN HO TRI8

---

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854528712	Folding box 1	69 mm x 1,174 mm x 77 mm	1245.00 g	6.24 dm <sup>3</sup>
4099854528729	Shipping box 6	1,184 mm x 225 mm x 170 mm	8125.00 g	45.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.