



LEDVANCE

# PRODUCT DATASHEET

## 5" 15W DF

LED VALUE DOWNLIGHT ALU GEN2 | Downlights



---

### Product benefits

- Selectable color temperature: 3000K or 4000K or 6500K
- Two versions for structure selection: diffuser version, reflector version
- Luminous flux output of up to 4200 lm
- IP54 rating for the front side of reflector version, indicating water resistance
- Flicker-free driver, ensuring a stable and comfortable lighting experience
- Safety compliance certificates: CB, EU RoHS 2.0, indicating adherence to safety and environmental regulations

## TECHNICAL DATA

## Electrical data

Nominal wattage	15.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Protection class	II

## Photometrical data

Color rendering index Ra	≥80
Beam angle	105 °

## Dimensions &amp; Weight

Diameter	113.00 mm
Length	145.00 mm
Height	74.00 mm
Product weight	200.00 g


## Materials &amp; Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

## Application &amp; Mounting

Type of protection	IP20/IP40
Dimmable	No
Mounting type	Recessed
Replaceable light source	No

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED VALUE DOWNLIGHT ALU GEN2

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854308437	Folding box 1	165 mm x 165 mm x 78 mm	250.00 g	2.12 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854308444	Shipping box 18	515 mm x 350 mm x 255 mm	4998.00 g	45.96 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.