

PRODUCT DATASHEET 5" 15W

LED VALUE DOWNLIGHT MODULE ALU | Downlights



Product benefits

- Selectable color temperature: 3000K or 4000K or 6500K
- Diffusor structure design
- Luminous flux output of up to 4200 lm
- Safety compliance certificates: CB, EU RoHS 2.0, indicating adherence to safety and environmental regulations

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	100277 V
Mains frequency	5060 Hz
Protection class	П

Photometrical data

Color rendering index Ra	≥80
Beam angle	105 °

Dimensions & Weight

	Diameter	145.00 mm
Ī	Height	74.00 mm
Ī	Product weight	130.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No

DOWNLOAD DATA

Documents and certificates		Document name	
PDF	User instruction / safety instructions	LED VALUE DOWNLIGHT MODULE ALU	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854318795	Folding box 1	165 mm x 165 mm x 78 mm	180.00 g	2.12 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854318801	Shipping box 18	515 mm x 350 mm x 255 mm	3738.00 g	45.96 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.