

PRODUCT DATASHEET

8" 26/35W

LED VALUE DOWNLIGHT MODULE ALU | Downlights



Product benefits

- Selectable color temperature: 3000K or 4000K or 6500K
- Diffuser structure design
- Luminous flux output of up to 4200 lm
- Safety compliance certificates: CB, EU RoHS 2.0, indicating adherence to safety and environmental regulations

TECHNICAL DATA

Electrical data

Nominal wattage	35.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Protection class	II

Photometrical data

Color rendering index Ra	≥80
Beam angle	105 °

Dimensions & Weight

Diameter	232.00 mm
Height	112.00 mm
Product weight	300.00 g


Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Replaceable light source	No

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED VALUE DOWNLIGHT MODULE ALU

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854318832	Folding box 1	247 mm x 247 mm x 95 mm	350.00 g	5.80 dm³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854318849	Shipping box 12	515 mm x 515 mm x 305 mm	4699.00 g	80.89 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.