



## PRODUCT DATASHEET

### ENDURA® Flood Adjustable 10W 840 Black

ENDURA® Flood Adjustable | Adjustable floodlights



#### Areas of application

- Outdoor
- Garages
- Building facades
- Garden houses

#### Product benefits

- Customer can adjust the light in all kind of directions according to his needs
- Easy installation thanks to fast connector, no need for manual wiring work

#### Product features

- Versatile adjustable bracket: Floodlight can rotate vertically and horizontally
- Easy possibility to mount on 90° edges thanks to corresponding mounting holes
- Homogenous illumination thanks to Panel look



---

**TECHNICAL DATA****Electrical data**


Nominal wattage	10.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	68.000 mA
Inrush current	0.068 A
Inrush current time $T_{h50}$	2840 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	72
Max. number of luminaires per miniature circuit breaker C16	154
Power factor $\lambda$	> 0.5
Protection class	I
Operating mode	Mains voltage

**Photometrical data**

Luminous flux	850 lm
Total luminous flux of contained light sources	1100 lm
Luminous efficacy	85 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcn
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Beam angle	120 °

**Dimensions & Weight**

Length	107.00 mm
Width	62.00 mm
Height	124.00 mm
Product weight	195.00 g



ENDURA FL ADJ 10W 4000K

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-30...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP65/IP65
Protection class IK (shock resistance)	IK05
Dimmable	No
Mounting type	Surface
Mounting location	Wall
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------




## Certificates &amp; Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	ENDURA FLOODLIGHT OSRAM
	Legal information	Safety insert G11219601
	Legal information	Informationstext 18 Abs 4 ElektroG

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854705892	Folding box 1	68 mm x 112 mm x 141 mm	225.00 g	1.07 dm <sup>3</sup>
4099854705908	Shipping box 12	357 mm x 292 mm x 174 mm	2865.00 g	18.14 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.