

PRODUCT DATASHEET P PAR 38 120 30 ° 14.5 W/2700 K E27

PARATHOM® DIM PAR38 | Dimmable LED reflector lamps PAR38 with retrofit screw base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Stepless dimming
- Very high dimmer compatibility, see also www.ledvance.com/dim
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps



Product features

- LED alternative to high voltage halogen lamps
- High color consistency: ≤ 6 SDCM
- Dimmable
- Base: E27
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80
- Lifetime up to 25,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	14.5 W
Construction wattage	14.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	120 W
Nominal current	66 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	≥ 0.70

Photometrical data

Luminous intensity	2500 cd
Luminous flux	1200 lm
Nominal useful luminous flux 90°	1035 lm
Luminous efficacy	82 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	2500 cd
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	30 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	134.00 mm
Diameter	122.00 mm
Maximum diameter	122 mm
Product weight	350.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

Capabilities

Dimmable	Voo	
Dimmable	165	

Certificates & Standards

Energy efficiency class	A 1)	
Energy consumption	15.00 kWh/1000h	
Photobiological safety group acc. to EN62778	RG1	

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LPPR38D12030 14
Energy labelling regulation data acc EU 2019/2015	

Light source cap-type (or other electric interface)	E27
Length	134.00 mm
Height	122.00 mm
Width	122.00 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	PARATHOM DIM PAR38 14.5 W 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075184558	Folding box 1	127 mm x 129 mm x 170 mm	450.00 g	2.79 dm ³
4058075184565	Shipping box 6	402 mm x 278 mm x 196 mm	3069.00 g	21.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.