

PRODUCT DATASHEET LED VALUE STICK 9 W/2700 K E26

LED VALUE STICK | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- Low energy consumption
- Attractive lamp appearance

Product features

- LED alternative to conventional lamps
- Mercury-free lamps



TECHNICAL DATA

Electrical data

| Nominal wattage | 9 W |
|--|---------|
| Construction wattage | 9.00 W |
| Nominal voltage | 220 V |
| Claimed equiv. conventional lamp power | 70 W |
| Nominal current | 40 mA |
| Type of current | AC |
| Operating frequency | 5060 Hz |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.90 |

Photometrical data

| Luminous flux | 950 lm |
|---|------------|
| Nominal useful luminous flux 90° | 950 lm |
| Luminous efficacy | 105 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |
| Rated LLMF at 6,000 h | 0.80 |

Light technical data

| Beam angle | 200 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight

| Overall length | 111.00 mm |
|------------------|-----------|
| Diameter | 40.40 mm |
| Maximum diameter | 40 mm |
| Product weight | 39.00 g |

Temperatures & operating conditions

All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown

for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

| Ambient temperature range | -20+40 °C | |
|--|-----------|---|
| Lifespan | | |
| Number of switching cycles | 100000 | |
| Lumen maintenance at end of service lifetime | 0.70 | _ |
| Rated lamp survival factor at 6,000 h | ≥ 0.80 | |
| Additional product data | | |
| Base (standard designation) | E26 | |
| Mercury content | 0.0 mg | |
| Mercury-free | Yes | |

Capabilities

Product remark

Certificates & Standards

| Energy efficiency class | A+ 1) | |
|--|----------------|--|
| Energy consumption | 9.00 kWh/1000h | |
| Photobiological safety group acc. to EN62778 | RG1 | |

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

| Order reference | LVSTICK 9W/827 | | |
|---|----------------|--|--|
| Energy labelling regulation data acc EU 2019/2015 | | | |
| Light source cap-type (or other electric interface) | E26 | | |
| Length | 111.00 mm | | |
| Height | 40.40 mm | | |
| Width | 40.40 mm | | |

DOWNLOAD DATA

| Photometric and lighting design files | | Document name | |
|---------------------------------------|----------------|--------------------------|--|
| | IES file (IES) | LED VALUE STICK 9W 6500K | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075251175 | Blister 1 | 139 mm x 65 mm x 42 mm | 53.00 g | 0.38 dm ³ |
| 4058075251182 | Shipping box 5 | 346 mm x 109 mm x 182 mm | 466.00 g | 6.86 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.