

PRODUCT DATASHEET LED VALUE STICK 10 W/2700 K E26

LED VALUE STICK | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- Low energy consumption
- Attractive lamp appearance

Product features

- LED alternative to conventional lamps
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220 V
Claimed equiv. conventional lamp power	75 W
Nominal current	47 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.90

Photometrical data

Luminous flux	1100 lm
Nominal useful luminous flux 90°	1060 lm
Luminous efficacy	110 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	111.00 mm
Diameter	40.40 mm
Maximum diameter	40 mm
Product weight	39.00 g

Temperatures & operating conditions

	PRODUCT DATASHEE	
Ambient temperature range	-20+40 °C	
Lifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h	≥ 0.80	
Additional product data		
Base (standard designation)	E26	
Mercury content	0.0 mg	
Mercury-free	Yes	
All technical parameters apply to the entire lamp / Due to the production process for light-emitting diodes, the typical values for the technical LED parameters are purely statistical values not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	A+ 1)	
Energy consumption	10.00 kWh/1000h	
Photobiological safety group acc. to EN62778	RG1	

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LVSTICK 10W/827		
Energy labelling regulation data acc EU 2019/2015			
Light source cap-type (or other electric interface)	E26		
Length	111.00 mm		
Height	40.40 mm		
Width	40.40 mm		

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED VALUE STICK 10W 6500K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075251236	Blister 1	139 mm x 65 mm x 42 mm	53.00 g	0.38 dm ³
4058075251243	Shipping box 5	346 mm x 109 mm x 182 mm	466.00 g	6.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.