

PRODUCT DATASHEET LED VALUE STICK 12 W/6500 K E26

LED VALUE STICK | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- Low energy consumption
- Attractive lamp appearance

Product features

- LED alternative to conventional lamps
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	220 V
Claimed equiv. conventional lamp power	100 W
Nominal current	55 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.90

Photometrical data

Luminous flux	1350 lm
Nominal useful luminous flux 90°	1350 lm
Luminous efficacy	112 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	116.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	49.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C	
Lifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h	≥ 0.80	
Additional product data		
Base (standard designation)	E26	
Mercury content	0.0 mg	

Base (standard designation)	E26
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmahla	No
Dimmable	No

Certificates & Standards

Energy efficiency class	A+ 1)
Energy consumption	12.00 kWh/1000h
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LVSTICK 12W/865
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E26

Light source cap-type (or other electric interface)	E26
Length	116.00 mm
Height	45.00 mm
Width	45.00 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED VALUE STICK 12W 6500K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075251250	Blister 1	146 mm x 76 mm x 50 mm	70.00 g	0.55 dm ³
4058075251267	Shipping box 5	341 mm x 108 mm x 205 mm	567.00 g	7.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.