

# PRODUCT DATASHEET LED VALUE STICK 12 W/3000 K G24d GEN3

LED VALUE STICK TruWave | LED lamps, classic stick shape with TruWave Technology™





# TECHNICAL DATA

# Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	26 W
Nominal current	90 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.50

# Photometrical data

Luminous flux	1250 lm
Nominal useful luminous flux 90°	1250 lm
Luminous efficacy	104 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	200 °
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	146.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	55.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

# Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Additional product data	
Base (standard designation)	G24d
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Type of protection	IP20
Standards	LVD
Photobiological safety group acc. to EN62778	RG0
Country-specific categorizations	
Order reference	LVSTICK 12W/830
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	G24d
Length	146.00 mm
Height	41.00 mm

# DOWNLOAD DATA

Width

	Photometric and lighting design files	Document name
ES S	IES file (IES)	IES files PIN STICK AC11979-12W 6500K 3000K

41.00 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075173798	Folding box 1	43 mm x 43 mm x 152 mm	69.00 g	0.28 dm <sup>3</sup>
4058075173804	Shipping box 10	222 mm x 93 mm x 168 mm	785.00 g	3.47 dm <sup>3</sup>
4099854316326	Shipping box 10	227 mm x 102 mm x 169 mm	860.00 g	3.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.