

## PRODUCT DATASHEET

### LED ECO STICK 7 W/2700 K B22d

LED ECO STICK | LED lamps, classic stick shape



#### Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

#### Product benefits

- Low energy consumption
- Attractive lamp appearance

#### Product features

- LED alternative to conventional lamps
- Mercury-free lamps
- Lifetime: up to 8,000 h



## TECHNICAL DATA

### Electrical data

Nominal wattage	7 W
Construction wattage	7.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	10 W
Nominal current	56 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

### Photometrical data

Luminous flux	550 lm
Nominal useful luminous flux 90°	550 lm
Luminous efficacy	78 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcn

### Light technical data

Beam angle	200 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	115.00 mm
Diameter	36.00 mm
Maximum diameter	36 mm
Product weight	25.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+30 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	100000
----------------------------	--------

### Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Standards	CB / RoHS
-----------	-----------

### Country-specific categorizations

Order reference	LECO STICK 7W/8
-----------------	-----------------

### LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	115.00 mm
Height	36.00 mm
Width	36.00 mm

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075667112	Folding box 1	42 mm x 42 mm x 117 mm	38.00 g	0.21 dm <sup>3</sup>
4058075667129	Shipping box 10	218 mm x 92 mm x 132 mm	450.00 g	2.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.