

PRODUCT DATASHEET

LED PERFORMANCE STICK 11 W/4000 K B22d

LED PERFORMANCE STICK | LED lamps, classic stick shape



Areas of application

- Suitable for indoor applications
- Replacement for conventional compact fluorescent lamps with wattage 11 W, 15 W and 24 W

Product benefits

- Creation of the preferred light ambience thanks to dimming
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- Stylish and modern design
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime: up to 25,000 h
- Mercury-free lamps
- Input voltage: 220...240 V_{AC}
- Storage temperature from -20 °C to up to +80 °C, up to 95 % relative humidity



– Operating temperature from -20 °C to up to +35 °C, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	77 W
Nominal current	68 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.70

Photometrical data

Luminous flux	1100 lm
Luminous efficacy	100 lm/W
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤ 6 sdc _m

Light technical data

Beam angle	200 °
Starting time	0.5 s

Dimensions & Weight

Overall length	115.00 mm
Diameter	40.00 mm
Maximum diameter	40 mm
Product weight	34.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+30 °C
---------------------------	--------------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	F
-------------------------	---

Country-specific categorizations

Order reference	LP STICK DIM11W
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	115.00 mm
Height	40.00 mm
Width	40.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075636286	Folding box 1	47 mm x 47 mm x 121 mm	48.00 g	0.27 dm ³
4058075636293	Shipping box 10	246 mm x 103 mm x 138 mm	579.00 g	3.50 dm ³
4099854275845	Shipping box 10	225 mm x 98 mm x 134 mm	567.00 g	2.95 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.