

# PRODUCT DATASHEET LED VALUE CLAS A 8 W/6500 K E27 GEN4

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- $-\,$  Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

### **Product features**

- Color rendering index  $R_a$ :  $\geq 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

## Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220240 V
Nominal current	62 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz

## Photometrical data

Luminous flux	806 lm
Luminous efficacy	100 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865

# Light technical data

Beam angle	180 °
------------	-------

# Dimensions & Weight

Overall length	105.00 mm
Diameter	59.00 mm
Product weight	20.00 g

# Temperatures & operating conditions

## Additional product data

	Base (standard designation)	E27	
Mercury-free		Yes	
	Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

## Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

## Country-specific categorizations

Order reference	LVCLA60 8W/865
Gradi Tolorono	2.00 (00 000,000

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	105.00 mm
Height	59.00 mm
Width	59.00 mm
EPREL ID	1403225
Model number	AC24710

#### **DOWNLOAD DATA**

Photometric and lighting design files		Document name	
lis lis	IES file (IES)	LED VALUE CLA60 8.5W 6500K	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075282827	Folding box 1	64 mm x 64 mm x 131 mm	55.00 g	0.54 dm <sup>3</sup>
4099854254765	Shipping box 10	332 mm x 138 mm x 147 mm	772.00 g	6.73 dm <sup>3</sup>
4058075282834	Shipping box 10	332 mm x 138 mm x 147 mm	704.00 g	6.73 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.