

PRODUCT DATASHEET LED VALUE CLAS B 25 3.3 W/2700 K E14

LED VALUE CLASSIC B | LED lamps, classic mini-candle shape



Areas of application

- General illumination
- Domestic applications
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Simple direct replacement for conventional incandescent lamps
- Instant 100 % light, no warm-up time

Product features

- LED alternative to conventional lamps
- Not dimmable
- $-\,$ Good color rendering CRI \geq 80 and color stability throughout the life of the lamp





TECHNICAL DATA

Electrical data

Nominal wattage	3.3 W
Construction wattage	3.30 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	25 W
Nominal current	28 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.50

Photometrical data

Luminous flux	250 lm
Nominal useful luminous flux 90°	250 lm
Luminous efficacy	75 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	220 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	100.00 mm
Diameter	37.00 mm
Maximum diameter	35 mm
Product weight	18.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C	
Lifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h	≥ 0.90	
Additional product data		
Base (standard designation)	E14	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	G ¹⁾	
Energy consumption	3.00 kWh/1000h	
Photobiological safety group acc. to EN62778	RG0	
Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E Country-specific categorizations	(lowest efficiency)	
Order reference	LVCLB253,3W/827	
Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	E14	
Correlated colour temperature type	SINGLE_VALUE	
Length	100.00 mm	
Height	37.00 mm	
Width	37.00 mm	
Displacement factor	0.5	
EPREL ID	1403236	
Model number	AC24723	

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075473522	Folding box	38 mm x 38 mm x 102 mm	28.00 g	0.15 dm ³
4058075473539	Shipping box 10	198 mm x 84 mm x 113 mm	339.00 g	1.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.