

PRODUCT DATASHEET

VALUE PAR 30 30 ° 15 W/2700 K E27

LED VALUE PAR30 | LED reflector lamps



Areas of application

- Hospitality
- Restaurants
- Commercial applications
- Residential interiors
- Museums, art galleries
- Offices

Product benefits

- Attractive lamp appearance
- Easy replacement of halogen lamps thanks to compact design
- Brilliant accent light
- Instant 100 % light, no warm-up time
- Very low energy consumption
- Easy installation

Product features

- Power factor: 0.95
- Low flicker light
- Luminaire efficacy: up to 83 lm/W
- Luminous flux: up to 1,250 lm



- High color consistency: < 6 SDCM
- Lifetime up to 15,000 h
- Suitable for general and accent lighting in shops and retail

TECHNICAL DATA**Electrical data**

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	220...240 V
Nominal current	68 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.95

Photometrical data

Luminous flux	1250 lm
Luminous efficacy	83 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤ 6 sdc _m

Light technical data

Beam angle	30 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	82.00 mm
Diameter	95.00 mm
Product weight	240.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
----------	----


Country-specific categorizations

Order reference	LVPAR30125 15W/
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	82.00 mm
Height	95.00 mm
Width	95.00 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LED VALUE PAR30 15W 2700K E27

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075137080	Folding box 1	99 mm x 99 mm x 140 mm	288.00 g	1.37 dm ³
4058075137097	Shipping box 10	511 mm x 210 mm x 159 mm	3216.00 g	17.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.