PRODUCT DATASHEET LED VALUE CLAS A FIL 4 W/2700 K B22d CL

LED VALUE CLASSIC A FILAMENT | LED lamps, classic bulb shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Correct operation even at low temperatures

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Lifetime up to 15,000 h
- Beam angle: up to 300°
- Lamp made of glass



– Good quality of light; color rendering index $R_{a:} \ge 80$; constant chromaticity

TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	35 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.40

Photometrical data

Luminous flux	470 lm	
Nominal useful luminous flux 90°	470 lm	
Luminous efficacy	117 lm/W	
Lumen main.fact.at end of nom.life time	0.70	
Light color (designation)	Warm White	
Color temperature	2700 K	
Color rendering index Ra	≥80	
Light color	827	
Standard deviation of color matching	≤6 sdcm	

Light technical data

Beam angle	300 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	104.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	31.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Number of switching cycles	100000		
Lumen maintenance at end of service lifetime	0.70		
dditional product data			
Base (standard designation)	B22d		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Clear		
Product remark	All technical parameters apply to the entire lamp / Due to the comproduction process for light-emitting diodes, the typical values sho for the technical LED parameters are purely statistical values that continuous not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		
Capabilities			
Dimmable	No		
Certificates & Standards			
Type of protection	IP20		
Country-specific categorizations			
Order reference	ference LV CLA 4W/827 2		
LOGISTICAL DATA			
Temperature range at storage	-20+80 °C		
Energy labelling regulation data acc EU 2019/2015			
Light source cap-type (or other electric interface)	B22d		
Length	104.00 mm		
Height	60.00 mm		
Width	60.00 mm		
EPREL ID	1403179,523220		
Model number	AC24355,AC32413		

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED CLASSIC A 4 W FIL non-dim 2700K

Photometric and lighting design files	Document name
LDT file (Eulumdat)	LV CLA 4W 827 230V FIL B22D
Light distribution curve type polar	LV CLA 4W 827 230V FIL B22D

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267183	Folding box 1	64 mm x 64 mm x 131 mm	49.00 g	0.54 dm ³
4099854259883	Shipping box 10	332 mm x 138 mm x 147 mm	637.00 g	6.73 dm ³
4058075506664	Shipping box 10	332 mm x 138 mm x 147 mm	637.00 g	6.73 dm ³
4058075751156	Shipping box 10	332 mm x 138 mm x 147 mm	637.00 g	6.73 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.