

PRODUCT DATASHEET LED PFM CLAS B FIL 5 W/2700 K E14

LED PERFORMANCE CLASSIC B FILAMENT | LED lamps, classic mini-ball shape, dimmable



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

Product features

- Beam angle: up to 300°
- Long lifetime up to 15,000 h
- Color rendering index R_a: ≥ 80





- High color consistency: < 6 SDCM
- Luminous efficacy: up to 95 lm/W
- Same appearance like conventional light bulb shape
- Mercury-free lamps
- Operating temperature from -20 °C to up to +40 °C, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	5 W
Construction wattage	5.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	25 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.70

Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	94 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	97.00 mm
Diameter	35.00 mm
Maximum diameter	35 mm
Product weight	13.00 g

Temperatures & operating conditions

	-20+40 °C		
ifespan			
Number of switching cycles	100000		
Lumen maintenance at end of service lifetime	0.70		
Rated lamp survival factor at 6,000 h	≥ 0.90		
Additional product data			
Base (standard designation)	E14		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Clear		
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		
Capabilities			
Dimmable	Yes		
Certificates & Standards			
Energy efficiency class	F 1)		
	F ¹⁾ 5.00 kWh/1000h		
Energy efficiency class			
Energy efficiency class Energy consumption	5.00 kWh/1000h RG0		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778 Description Description Description Photobiological safety group acc. to EN62778	5.00 kWh/1000h RG0		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778 Description: Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations)	5.00 kWh/1000h RG0 (lowest efficiency)		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations Order reference	5.00 kWh/1000h RG0 (lowest efficiency)		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778 Denergy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations) Order reference Energy labelling regulation data acc EU 2019/2015	5.00 kWh/1000h RG0 (lowest efficiency) LPCLB 5W/827 23		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778 Denergy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations) Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface)	5.00 kWh/1000h RG0 (lowest efficiency) LPCLB 5W/827 23		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations) Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type	5.00 kWh/1000h RG0 (lowest efficiency) LPCLB 5W/827 23 E14 SINGLE_VALUE		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778 Denergy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations) Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type Length	5.00 kWh/1000h RG0 (lowest efficiency) LPCLB 5W/827 23 E14 SINGLE_VALUE 97.00 mm		
Energy efficiency class Energy consumption Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (Country-specific categorizations) Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type Length Height	5.00 kWh/1000h RG0 (lowest efficiency) LPCLB 5W/827 23 E14 SINGLE_VALUE 97.00 mm 35.00 mm		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075506701	Folding box 1	39 mm x 39 mm x 109 mm	27.00 g	0.17 dm ³
4058075506718	Shipping box 10	205 mm x 87 mm x 123 mm	318.00 g	2.19 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.