

PRODUCT DATASHEET HAL CLASSIC P 28W 240V B22d

HALOGEN CLASSIC P | Halogen lamps, classic mini-ball shape



Areas of application

- General illumination
- Mood lighting
- Entrance lighting
- Mirror lighting

Product benefits

- Simple direct replacement for conventional incandescent lamps
- The same pleasant quality of light as that of an incandescent lamp
- Instant 100 % light, no warm-up time
- Contains no mercury
- UV filter

Product features

- Average life: 2,000 h
- 100 % dimmable
- Perfect color rendering (Ra: 100)

TECHNICAL DATA

Electrical data

Nominal wattage	28 W
Construction wattage	28.00 W
Nominal voltage	240 V
Nominal current	0.12 A

Photometrical data

Luminous flux	360 lm
Luminous efficacy	12 lm/W
Color temperature	2700 К
Color rendering index Ra	100
Light color	1027

Dimensions & Weight

Overall length	72.00 mm
Diameter	45.00 mm
Product weight	19.6 g

Additional product data

Base (standard designation) B22d

Country-specific categorizations

Order reference	CLAS P CL 28W 2

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	72.00 mm
Height	45.00 mm
Width	45.00 mm

Safety advice

- Do not touch the lamp if broken.

- Must not be used if outer bulb is defective.

- Lamp to be used only in a closed luminaire.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854041068	Folding box 2	82 mm x 46 mm x 74 mm	75.00 g	0.28 dm ³
4099854041075	Shipping box 20	236 mm x 170 mm x 84 mm	834.00 g	3.37 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.