

# PRODUCT DATASHEET HALOPIN 25 W 230 V G9

HALOPIN® Standard | Halogen lamps with G9 base



#### Areas of application

- General illumination
- Workplace lighting
- Lighting for reading
- Dining table lighting
- Mirror lighting
- Accent lighting
- Mood lighting

### **Product benefits**

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Robust filament design thanks to innovative, unique bulb pinch technology
- Approved for use in open luminaires (to IEC 60598-1)
- Simple handling thanks to G9 plug-in base/holder system
- No transformer required
- UV filter
- Complies with IEC 60432-3 thanks to integrated fuse function
- The lamp shuts down reliably
- Contains no mercury

#### **Product features**

- Average life: 2,000 h
- Dimmable
- Color rendering index Ra: 100
- Design: two lengths 43 mm (short), 51 mm (long)

- Base: G9
- Color temperature: 2,700 K

# TECHNICAL DATA

### Electrical data

Nominal wattage	25 W
Construction wattage	25.00 W
Nominal voltage	230 V

# Photometrical data

Luminous flux	230 lm
Luminous efficacy	9 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

# Light technical data

# Dimensions & Weight

Overall length	43.00 mm
Diameter	14.00 mm
Product weight	3.00 g

# Additional product data

Base (standard designation)	G9
Mercury-free	Yes
Design / version	Tube

# Capabilities

Dimmable	Yes
Burning position	Any

# Country-specific categorizations

Order reference	66825 25W 230V
-----------------	----------------

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G9
Length	43.00 mm
Height	14.00 mm
Width	14.00 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321329844	Folding box 1	25 mm x 23 mm x 70 mm	6.00 g	0.04 dm <sup>3</sup>
4008321329851	Bundle 10	115 mm x 50 mm x 70 mm	60.00 g	0.40 dm <sup>3</sup>
4008321329868	Shipping box 200	272 mm x 238 mm x 155 mm	1453.00 g	10.03 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.