

PRODUCT DATASHEET

HALOPAR 30 75 W 230 V 30° E27

HALOPAR® 30 | Halogen lamps with parabolic reflector PAR30, with screw base



Areas of application

- General illumination
- Workplace lighting
- Kitchen lighting
- Object lighting
- Accent lighting
- Shops
- Restaurants, hotels and similar prestigious applications

Product benefits

- Brilliant accent light
- With whole glass reflector for brilliant lighting effects
- Instant 100 % light, no warm-up time
- Approved for use in open luminaires (to IEC 60598-1)
- Contains no mercury
- UV filter

Product features

- Average life: 2,000 h
- 100 % dimmable
- Perfect color rendering (R_a : 100)
- Color temperature: 2,900 K


TECHNICAL DATA

Electrical data

Nominal wattage	75 W
Construction wattage	75.00 W
Nominal voltage	230 V

Photometrical data

Luminous intensity	6900 cd
Light color (designation)	Warm White
Color temperature	2900 K
Color rendering index Ra	100
Light color	1029



349634_HAL_HV_AK

Light technical data

Beam angle	30 °
Starting time	0 s

Dimensions & Weight

Overall length	90.50 mm
Diameter	97.0 mm
Product weight	175.00 g

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Design / version	Reflector
Product remark	Not suitable for outdoor use or damp conditions / Banned from 1.9.2016 as per EU phase-out plan

Capabilities

Dimmable	Yes
----------	-----

Burning position	Any
------------------	-----


Country-specific categorizations

ILCOS	HAGS/UB-75-230-E27-97/30
Order reference	64841 SST FL

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	90.50 mm
Height	97.0 mm
Width	97.0 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
 Spectral power distribution	349634_HAL_HV_AK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321286345	Folding box 1	90 mm x 90 mm x 106 mm	206.00 g	0.86 dm ³
4008321286352	Shipping box 15	471 mm x 287 mm x 136 mm	3801.00 g	18.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.