

# PRODUCT DATASHEET HALOSPOT 111 50 W 12 V 24° G53

HALOSPOT® 111 | Halogen spot lamps with 111 mm aluminum reflector



#### Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Entrance lighting

#### Product benefits

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Burner with axial filament for optimum distribution of light
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in luminaire thanks to aluminum-coated reflector
- Contains no mercury

#### Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index Ra: 100



- Diameter: 111 mm


# TECHNICAL DATA

# Electrical data

Nominal wattage	50 W
Construction wattage	50.00 W
Nominal voltage	12 V

# Photometrical data

Luminous intensity	4000 cd
Luminous flux	510 lm
Nominal useful luminous flux 90°	510 lm
Luminous efficacy	10 lm/W
Lumen main.fact.at end of nom.life time	0.75
Light color (designation)	Warm White
Color temperature	2950 K
Color rendering index Ra	100
Light color	1029
Rated peak intensity	4000 cd
UV protection	Yes



349627\_HAL\_UVS\_ALU

# Light technical data

Beam angle	24 °
Starting time	0 s

# Dimensions & Weight

Overall length	61.00 mm
Diameter	111,0 mm
Maximum diameter	111 mm

Product weight	50.17 g		
ifespan			
Number of switching cycles	100000		
Additional product data			
Base (standard designation)	G53		
Mercury-free	Yes		
Design / version	Reflector		
Product remark	If connectors are used, an additional holder is required at the rim of the reflector / May produce noise in combination with some dimmers.  Recommended solution: use OSRAM HTi DALI 150/230-240 DIM with OSRAM DALI MCU		
Capabilities			
Dimmable	Yes		
Burning position	Any		
Certificates & Standards			
Energy efficiency class	G		
Energy consumption	54.00 kWh/1000h		
Country-specific categorizations			
ILCOS	HMGS//UB-50-12-G53-111/24		
Order reference	41835 FL		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	OTHER		
Non-directional or directional	DLS		
Mains or non-mains	NMLS		
Light source cap-type (or other electric interface)	G53		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	No		
High luminance light source	No		
Anti-glare shield	Yes		
Correlated colour temperature type	SINGLE_VALUE		
	67.00 mm		
Length	67.00 Min		

Width	111,0 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle correspondence	NARROW_CONE_90
EPREL ID	1337633
Model number	AB47627

#### DOWNLOAD DATA

Photometric and lighting design files	Document name	
Spectral power distribution	349627_HAL_UVS_ALU	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300011769	Folding box	112 mm x 86 mm x 87 mm	81.15 g	0.84 dm <sup>3</sup>
4050300244495	Shipping box 6	275 mm x 130 mm x 185 mm	615.90 g	6.61 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.