

PRODUCT DATASHEET DST MITW 15 W/4000 K 220...240 V B22d

OSRAM DULUXSTAR® MINI TWIST | Compact fluorescent integrated, spiral shape



Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

Product benefits

- Fast return on investment
- Compact dimensions
- Up to 80 % less energy consumption compared with ordinary light bulbs

Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	220240 V
Nominal current	150 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	0.50

Photometrical data

Luminous flux	900 lm
Color temperature	4000 K
Color rendering index Ra	80
Light color	840

Light technical data

Warm-up time (60 %)	< 60.00 s
Starting time	≤ 1.5 s

Dimensions & Weight

Overall length	105.00 mm
Diameter	41.00 mm
Tube diameter	T2
Maximum diameter	52 mm
Product weight	55.00 g

Lifespan

Number of switching cycles	≥10000
----------------------------	--------

Additional product data

Base (standard designation)	B22d
Mercury content	2.0 mg
Mercury-free	No

Country-specific categorizations

Order reference	DST MTW 15W/840
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	102.00 mm
Height	41.00 mm
Width	41.00 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
- Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899109315	Folding box 1	43 mm x 43 mm x 114 mm	66.00 g	0.21 dm ³
4058075029590	Shipping box 12	268 mm x 94 mm x 131 mm	880.00 g	3.30 dm ³
4052899146105	Shipping box 12	268 mm x 94 mm x 131 mm	880.00 g	3.30 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

B22d