

## PRODUCT DATASHEET

### HQI-T 2000W/N 2

POWERSTAR HQI®-T 1000...2000 W | Metal halide lamps for enclosed luminaires



#### Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Airports
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High efficiency
- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

#### Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



## TECHNICAL DATA

### Electrical data

Nominal wattage	2000 W
Nominal voltage	116 V
Ignition voltage	0.75/1.3 kVp
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	18.8 A
PFC capacitor at 50 Hz	125 µF

### Photometrical data

Luminous flux	190000 lm
Luminous efficacy	93 lm/W
Color temperature	4150 K
Color rendering index Ra	60
Light color	641
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.85
Rated lamp efficacy (standard co.)	93 lm/W
UV protection	Yes

### Dimensions & Weight

Overall length	430.00 mm
Length	430.00 mm
Light center length (LCL)	265,0 mm
Diameter	106.00 mm
Maximum diameter	106 mm
Product weight	580.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Rated lamp survival factor at 2,000 h	0.88
Rated lamp survival factor at 4,000 h	0.58

Rated lamp survival factor at 6,000 h	0.38
Lifespan B50	4500 h

Additional product data

Base (standard designation)	E40
Mercury content	130.0 mg
Design / version	Clear
Product remark	Not for general lighting / Lamp ignites at an ignition voltage of 0.9...1.3 kVs; lamps must not be operated with 4...5 kV igniters

Capabilities

Dimmable	No
Burning position	p30
Enclosed luminaire required	Yes
Hot restart	No





Certificates & Standards

Energy consumption	2244.00 kWh/1000h
--------------------	-------------------

Country-specific categorizations

Order reference	HQI-T 2000W/N 2
-----------------	-----------------

DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	High Intensity Discharge Lamp UI
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4082707-EN-00 - HQI 1000W-2000W
	Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075389526	Round wrap 1	465 mm x 130 mm x 130 mm	775.00 g	7.86 dm³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075389533	Shipping box 4	275 mm x 270 mm x 525 mm	3724.00 g	38.98 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.