

## PRODUCT DATASHEET

### HQI-T 1000W/N E

POWERSTAR HQI®-T 1000...2000 W | Metal halide lamps for enclosed luminaires



#### Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Airports
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High efficiency
- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

#### Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



## TECHNICAL DATA

### Electrical data

Nominal wattage	1000 W
Nominal voltage	130 V
Ignition voltage	4.0/5.0 kVp
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	9 A
PFC capacitor at 50 Hz	85 $\mu$ F

### Photometrical data

Luminous flux	110000 lm
Luminous efficacy	104 lm/W
Color temperature	3350 K
Color rendering index Ra	64
Light color	633
Rated LLMF at 2,000 h	0.91
Rated LLMF at 4,000 h	0.86
Rated LLMF at 6,000 h	0.82
Rated LLMF at 8,000 h	0.78
Rated LLMF at 12,000 h	0.70
Rated lamp efficacy (standard co.)	104 lm/W
UV protection	Yes

### Dimensions & Weight

Overall length	345.00 mm
Length	345.00 mm
Light center length (LCL)	220,0 mm
Diameter	82.00 mm
Maximum diameter	76 mm
Product weight	413.5 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.95
Rated lamp survival factor at 6,000 h	0.83
Rated lamp survival factor at 8,000 h	0.62
Rated lamp survival factor at 12,000 h	0.16
Lifespan B50	9000 h

### Additional product data

Base (standard designation)	E40
Mercury content	110.0 mg
Design / version	Clear
Product remark	Not for general lighting

### Capabilities

Dimmable	No
Burning position	p30
Enclosed luminaire required	Yes
Hot restart	No





### Certificates & Standards


Energy consumption	1160.50 kWh/1000h
--------------------	-------------------

### Country-specific categorizations

ILCOS	MT/UB-1000/635-H/E/SL-E40-76/345/H
Order reference	HQI-T 1000W/N E

### DOWNLOAD DATA

	Documents and certificates	Document name
	User Instruction / Safety Instructions	High Intensity Discharge Lamp UI
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4082707-EN-00 - HQI 1000W-2000W
	Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH

Photometric and lighting design files	Document name
 Spectral power distribution	384078_HQI_T_N_E40

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075388413	Round wrap 1	750 mm x 375 mm	483.50 g	
4058075388420	Shipping box 6	440 mm x 300 mm x 210 mm	3475.00 g	27.72 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.