

PRODUCT DATASHEET HE 35 W/865

LUMILUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency, with G5 base



Areas of application

- Public buildings
- Offices
- Shops
- Supermarkets and department stores
- Industry
- Outdoor applications only in suitable luminaires

Product benefits

– Up to 20 % more economical than LUMILUX® T8

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable






TECHNICAL DATA

Electrical data

Nominal wattage	35 W
Construction wattage	35.50 W
Rated lamp efficacy (HF data 25 °C)	86

Photometrical data

Luminous flux	3050 lm
Luminous efficacy	86 lm/W
Luminous flux at 25 °C	3050 lm
Luminous flux at 35 °C	3500 lm
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	86



Dimensions & Weight

Overall length	1449.00 mm
Length with base excl. base pins/connection	1449 mm

Diameter	16,0 mm		
Tube diameter	16 mm		
Maximum diameter	16 mm		
Product weight	115.00 g		
Temperatures & operating conditions			
Rated ambient temp.w.max.luminous			
Lifespan			
Service life	19000 h ¹⁾		
Rated lamp survival factor at 2,000 h	0.99		
Rated lamp survival factor at 4,000 h	0.99		
Rated lamp survival factor at 6,000 h	0.99		
Rated lamp survival factor at 8,000 h	0.99		
Rated lamp survival factor at 12,000 h	0.99		
Rated lamp survival factor at 16,000	0.97		
Rated lamp survival factor at 20,000 h	0.85		
Operation mode LLMF/LSF	HF		
1) With preheat ECG			
Additional product data			
Base (standard designation)	G5		
Mercury content	1.2 mg		
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 3040 °C; optimum luminous flux achieved at 35 °C		
Capabilities			
Suitable for indoor	Yes		
Dimmable	Yes		
Certificates & Standards			
Energy efficiency class	A+		
Energy consumption	39.05 kWh/1000h		
Country-specific categorizations			

FDH-35/865-L/P/-G5-16/1449

ILCOS

Order reference	HE 35W/865
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LFL_T5_HE
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Envelope	No
Length	1449.00 mm
Height	16,0 mm
Width	16,0 mm
Beam angle correspondence	SPHERE_360

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

Photometric and lighting design files	Document name	
Spectral power distribution	349641_FL_865	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300464664	Unpacked 1	1,461 mm x 15 mm x 15 mm	132.00 g	0.33 dm ³
4050300464671	Shipping box 40	1,496 mm x 199 mm x 87 mm	5182.00 g	25.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.