PRODUCT DATASHEET HO 24 W/827

LUMILUX® T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

Product benefits

– Up to 20 % more economical than LUMILUX® T8

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable






TECHNICAL DATA

Electrical data

Nominal wattage	24 W
Construction wattage	22.40 W
Nominal voltage	77 V
Nominal current	0.3 A

Photometrical data

Luminous efficacy 89 Im/W Luminous flux at 25 °C Array Luminous flux at 35 °C 2000 Im Light color (designation) LUMILUX INTERNA Color temperature 2700 K Color rendering index Ra 880 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.92 Rated LLMF at 6,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90 Rated LLMF at 16,000 h 0.90 Rated LLMF at 20,000 h 0.90 Rated LLMF at 20,000 h 0.90		
Luminous flux at 25 °C Array Luminous flux at 35 °C 2000 lm Light color (designation) LUMILUX INTERNA Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Luminous flux	2000 lm
Luminous flux at 35 °C 2000 Im Light color (designation) LUMILUX INTERNA Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Luminous efficacy	89 lm/W
Light color (designation) LUMILUX INTERNA Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Luminous flux at 25 °C	Array
Color temperature 2700 K Color rendering index Ra ≥80 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Luminous flux at 35 °C	2000 lm
Color rendering index Ra ≥80 Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Light color (designation)	LUMILUX INTERNA
Light color 827 Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Color temperature	2700 K
Rated LLMF at 2,000 h 0.95 Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Color rendering index Ra	≥80
Rated LLMF at 4,000 h 0.93 Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Light color	827
Rated LLMF at 6,000 h 0.92 Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Rated LLMF at 2,000 h	0.95
Rated LLMF at 8,000 h 0.90 Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Rated LLMF at 4,000 h	0.93
Rated LLMF at 12,000 h 0.90 Rated LLMF at 16,000 h 0.90	Rated LLMF at 6,000 h	0.92
Rated LLMF at 16,000 h 0.90	Rated LLMF at 8,000 h	0.90
	Rated LLMF at 12,000 h	0.90
Rated LLMF at 20,000 h 0.89	Rated LLMF at 16,000 h	0.90
	Rated LLMF at 20,000 h	0.89



Dimensions & Weight

Overall length	563.20 mm
Length with base excl. base pins/connection	549,00 mm

16,0 mm	
16 mm	
44.26 g	
	16 mm

Service life	19000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85
Lifespan B50	24000 h

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G5
Mercury content	2.0 mg
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 3040 °C; optimum luminous flux achieved at 35 °C

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	24.00 kWh/1000h

Country-specific categorizations

ILCOS	FDH-24/827-L/P/-G5-16/549
Order reference	HO 24W/827

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LFL_T5_HO
Non-directional or directional	NDLS

Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	563.20 mm
Height	16,0 mm
Width	16,0 mm
Chromaticity coordinate x	0,463
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546277
Model number	AC34041

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077889-EN-00 - T5 HE HO
PDF	Certificates	EAC N RU D-DE.MU62.B.00801_20 02.03.2020-01.03.2025 Prommash Test - FL
PDF	Certificates	EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL
	Photometric and lighting design	n files Document name

Photometric and lighting design files	Document name
Spectral power distribution	349636_FL_827

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300646077	Sleeve 1	18 mm x 18 mm x 563 mm	67.50 g	0.18 dm ³
4050300646084	Shipping box 20	591 mm x 104 mm x 88 mm	1473.00 g	5.41 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.