

PRODUCT DATASHEET L 18 W/3000 K

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	18 W	
Construction wattage	18.00 W	
Nominal voltage	220 V	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

Photometrical data

Luminous flux at 25 °C	1350 lm	
Color temperature 3000 K		
Color rendering index Ra	> 80	
Light color	830	
ated lamp efficacy (HF data 25 °C) Under clarification by authority and standardization body		

Dimensions & Weight

Overall length	600.00 mm
Length with base excl. base pins/connection	590,00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	90.00 g

Lifespan

Service life	18000 h ¹⁾

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	4.5 mg

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference L 18W/830LUMILU	
---------------------------------	--

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	600.00 mm
Height	26.00 mm
Width	26.00 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321691187	Sleeve 1	605 mm x 27 mm x 27 mm	102.00 g	0.44 dm ³
4008321691194	Shipping box 25	646 mm x 151 mm x 153 mm	2772.00 g	14.92 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.