

## PRODUCT DATASHEET ST 171 SAFETY DEOS

Starters for single operation at 230 V AC (ST 111, ST 171, ST 173) | Starters for single operation at 230 V AC



---

### Product features

- Temperature range for reliable cut-out: -20...+80 °C



## TECHNICAL DATA

### Electrical data

Nominal wattage	65.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

### Dimensions & Weight

Diameter	21,5 mm
Product weight	8.64 g

### Additional product data

Mercury content	0.0 mg
Product remark	Temperature range for reliable switch-off: -20...+80 °C

### Capabilities

Dimmable	No
----------	----


### Country-specific categorizations

Order reference	ST171SAFETY/220
-----------------	-----------------

### Energy labelling regulation data acc EU 2019/2015

Length	40.30 mm
Height	21,5 mm
Width	21.50 mm

## DOWNLOAD DATA

Documents and certificates	Document name
 Declarations of conformity	Glow starter for fluorescent lamps

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300854106	Unpacked 1	37 mm x 19 mm x 22 mm	9.80 g	0.02 dm <sup>3</sup>
4050300422855	Unpacked 1	35 mm x 18 mm x 20 mm	8.64 g	0.01 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300797823	Tray 25	111 mm x 43 mm x 113 mm	232.80 g	0.54 dm <sup>3</sup>
4050300797830	Shipping box 200	227 mm x 98 mm x 227 mm	2020.00 g	5.05 dm <sup>3</sup>
4050300422862	Shipping box 1,200	400 mm x 265 mm x 325 mm	11169.00 g	34.45 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.