

PRODUCT DATASHEET MS-SV INF-CR 360 220-240 V IP20

LED VALUE PIR Motion Sensor | Sensors with infrared technology



Areas of application

- Suitable for indoor applications.
- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings

Product features

- 360° motion sensor (passive infrared technology)
- Ceiling surface and recessed mounting
- Timer function
- Adjustable illuminance from 3 or 10 lx to 2000 lx via knob switch (model dependent)
- Photocell detector available for daylight detection
- Input voltage: 220...240 V_{AC}
- Operating frequency: 50/60 Hz
- Ambient temperature in operation: -20...+40 °C
- Type of protection: IP20

TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Type of current	AC
Mains frequency	5060 Hz
Surge capability (L-N)	1 kV

Dimensions & Weight

Length	76.00 mm
Width	61.50 mm
Height	76.00 mm
Product weight	82.2 g

Colors & materials

Temperatures & operating conditions

Ambient temperature range	-20+45 °C

Capabilities

Dimmable	No
Maximum installation height	2.24 m
Detection area	6 m ¹⁾
Detection angle	360 °

¹⁾ Maximum diameter

Certificates & Standards

Protection class	П
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-35+55 °C
------------------------------	-----------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075383258	Folding box	80 mm x 80 mm x 86 mm	108.00 g	0.55 dm ³
4058075383265	Shipping box 10	412 mm x 172 mm x 108 mm	1270.00 g	7.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.